

IN THE CLAIMS

RECEIVED
CENTRAL FAX CENTER
NOV 19 2007

1.-9. (cancelled)

10. (currently amended) A method, comprising:

connecting an elongated member to a connection member, said connection member having a first channel and a second channel, so that at least part of said elongated member occupies at least part of said first channel;

sliding an offsetting member over said connection device so that at least a part of said offsetting member is between at least a part of said first channel and at least a part of said second channel;

connecting a bone fixation member to said connection member so that at least part of said bone fixation member occupies at least part of said second channel; and

applying compressive force to said elongated member, said offsetting member, and said ~~spinal fastener~~ bone fixation member.

wherein said offsetting member contacts said elongated member and said ~~spinal fastener~~ bone fixation member in at least two differing locations.

11. (currently amended) The method of claim 9 10, wherein said offsetting member has a ring shape.

12. (currently amended) The method of claim 9 10, wherein said offsetting member further includes at least two differing inner diameters.

13. (currently amended) The method of claim 9 10, wherein said offsetting member is composed of a shape memory alloy.

RESPONSE FOLLOWING ADVISORY ACTION

App. Ser. No. 10/824,752

Atty. Dkt. No. 4002-1675

Page 2 of 11

14. (currently amended) The method of claim ~~9~~ 10, wherein said offsetting member further includes at least one groove.
15. (cancelled)
16. (currently amended) The method of claim ~~15~~ 39, wherein said offsetting member has a ring shape.
17. (currently amended) The method of claim ~~15~~ 39, wherein said offsetting member further includes at least two differing inner diameters.
18. (currently amended) The method of claim ~~15~~ 39, wherein said offsetting member is composed of a shape memory alloy.
19. (currently amended) The method of claim ~~15~~ 39, wherein said offsetting member further includes at least one groove.
20. (currently amended) The method of claim ~~15~~ 39, wherein said locking member is a set screw, and said aperture is a threaded bore and intersects said second channel.
21. (original) The method of claim 20, wherein said threaded bore is arranged at an angle relative to a line between said first channel and said second channel.
- 22.-30. (cancelled)

RESPONSE FOLLOWING ADVISORY ACTION
App. Ser. No. 10/824,752
Atty. Dkt. No. 4002-1675
Page 3 of 11

31. (currently amended) The apparatus of claim 22 37, wherein said bone fixation member includes a threaded member.

32. (currently amended) The apparatus of claim 22 37, wherein said bone fixation member includes a hook.

33. (currently amended) The apparatus of claim 22 37, wherein said bone fixation member includes a clamp.

34. (currently amended) ~~The apparatus of claim 1~~ A connection device for connecting a spinal fastener to an elongated member comprising:

a body having a first end, a second end, a first channel, a second channel, and a third channel, said body having a portion that tapers outwardly towards said second end;

a washer slidably mountable over said body, said washer having a groove and an inner surface, wherein said inner surface has a diameter smaller than a diameter of the tapered portion of said body;

an offsetting member slidable over said first end, wherein said offsetting member contacts said spinal fastener in at least two locations; and

a fixation member insertable in said third channel, wherein the fixation member applies a compressive force preventing relative motion between the spinal fastener and the elongated member, wherein the entirety of said offsetting member is between a central longitudinal axis of the spinal fastener and a central longitudinal axis of the elongated member.

RESPONSE FOLLOWING ADVISORY ACTION

App. Ser. No. 10/824,752

Att. Dkt. No. 4002-1675

Page 4 of 11

35. (currently amended) The apparatus of claim ~~1~~ 34, wherein a portion of said body extends through said offsetting member.

36. (cancelled)

37. (currently amended) ~~The apparatus of claim 22~~ An apparatus, comprising:
a body member having a first channel and a second channel;
an elongated member at least partially within said first channel;
a bone fixation member at least partially within said second channel;
an offsetting member slidably connected to said body member and positioned between
said elongated member and said bone fixation member; and
a washer having a groove, said washer connected to said body so that said groove
accommodates at least a portion of said bone fixation member, wherein a portion of said body
member extends through said offsetting member.

38. (cancelled)

39. (currently amended) ~~The method of claim 15~~ A method, comprising:
providing a body having a first end, a second end, a first channel, a second channel, and
an aperture, wherein a portion of said body tapers outwardly;
sliding a washer over said body;
passing a fastener through said body via said first channel; and
sliding an offsetting member over said body, wherein said offsetting member engages
said fastener in at least two locations;

RESPONSE FOLLOWING ADVISORY ACTION
App. Ser. No. 10/824,752
Atty. Dkt. No. 4002-1675
Page 5 of 11

placing said body over said elongated member via said second channel; and
inserting a locking member into said aperture thereby locking said fastener with
respect to said elongated member.

wherein said washer has an opening, and said sliding of said washer includes having said washer opening substantially perpendicular to said first channel.

40. (new) The apparatus of claim 37, wherein said offsetting member further includes at least two differing inner diameters.

41. (new) The apparatus of claim 37, wherein said offsetting member further includes at least one groove.

42. (new) The apparatus of claim 37, further comprising a locking member connected to said body.

43. (new) The apparatus of claim 42, wherein said locking member is a set screw.

44. (new) The apparatus of claim 37, wherein said body member has a flat surface on either side of said body member.

45. (new) The apparatus of claim 37, wherein said washer has a first outer surface and a second outer surface, said first outer surface having a diameter that is smaller than a diameter of said second outer surface.

RESPONSE FOLLOWING ADVISORY ACTION

App. Ser. No. 10/824,752

Atty. Dkt. No. 4002-1675

Page 6 of 11

46. (new) The apparatus of claim 34, wherein said offsetting member further includes at least two differing inner diameters.

47. (new) The apparatus of claim 34, wherein said offsetting member further includes at least one groove.

48. (new) The apparatus of claim 34, wherein said fixation member is a set screw.

49. (new) The apparatus of claim 34, wherein said body member has a flat surface on either side of said body member.

50. (new) The apparatus of claim 34, wherein said washer has a first outer surface and a second outer surface, said first outer surface having a diameter that is smaller than a diameter of said second outer surface.

51. (new) The apparatus of claim 34, wherein said offsetting member has a ring shape.

52. (new) The apparatus of claim 34, wherein said offsetting member is composed of a shape memory alloy.

53. (new) The apparatus of claim 34, wherein said fastener includes a threaded member.

54. (new) The apparatus of claim 34, wherein said fastener is a Schanz-type screw.

55. (new) The apparatus of claim 34, wherein said fastener includes a hook.

RESPONSE FOLLOWING ADVISORY ACTION

App. Ser. No. 10/824,752

Atty. Dkt. No. 4002-1675

Page 7 of 11

56. (new) The apparatus of claim 34, wherein said fastener includes a clamp.
57. (new) The apparatus of claim 37, wherein said offsetting member has a ring shape.
58. (new) The apparatus of claim 37, wherein said offsetting member is composed of a shape memory alloy.

RESPONSE FOLLOWING ADVISORY ACTION
App. Ser. No. 10/824,752
Atty. Dkt. No. 4002-1675
Page 8 of 11